Job Name/Location: Tag #: For: File Date: Resubmit PO No.: Approval Other GC: Architect: Mech: Engr: Rep: (Company) (Project Manager)







LA240HYV1

Art Cool™ Prestige Single Zone Inverter

Outdoor Unit (ODU) - LAU240HYV1 Indoor Unit (IDU) - LAN240HYV1

Performance:

Cooling:

Capacity (Min-Rated-Max, Btu/h)	3,070-22,000-30,000
SEER	22
EER	12.50

SEER - Seasonal Energy Efficiency Ratio EER - Energy Efficiency Ratio

Heating:

Capacity (Min-Rated-Max, I	3,070-27,000-35,200
HSPF	12

HSPF - Heating Seasonal Performance Factor

Power Supply (V1/Hz/Ø)

Cooling Nominal Test Conditions: Heating Nominal Test Conditions: Indoor: 80°F DB/67°F WB Indoor: 70°F DB/60°F WB Outdoor: 95°F DB/75°F WB Outdoor: 47°F DB/43°F WB

Electrical:

Outdoor Unit:	
MOP (A)	25
MCA (A)	19
Cooling Rated Amps (A)	15.3
Heating Rated Amps (A)	15.3
Compressor (A)	14.5

MOP - Maximum Overcurrent Protection MCA - Minimum Circuit Ampacity

Total Power Input:

Fan Motor (A)

Cooling Power Input (kW)	1.76
Heating Power Input (kW)	2.19

Piping:

Liquid Line (in, OD)	3/8
Vapor Line (in, OD)	5/8
Additional Refrigerant (oz/ft)	0.38
Min/Max Pipe Length (ft) ² :	9.8/98.4
Piping Length (no add'l refrigerant, ft)	24.6
Max Elevation (ft)	65.6

ntrole Foatures

•Built-in low ambient

operation to 14°F

Chaos wind

controls reatures:	
•24-Hour on/off timer	 Condensate sensor
4-Way auto swing	connection
 Auto changeover 	 Defrost control
•Auto restart	 Dehumidifying mode

Jet cool/Jet heat •Self cleaning indoor coil

- Self diagnosis
- •Sleep mode
- Soft dry operation

208-230/60/1

0.5

- •Ultra quiet operation
- Cooling only switch
- •3M Micro Protection Filter
- •Smart AC module

Optional Accessories (sold separately):

PI-485 - PMNFP14	Α1
------------------	----

LG Programmable Thermostat - PREMTB10U

■ Dry Contact for third party thermostat - PDRYCB300

Hot start

Low Ambient Kit: PQCA0 adapter, PAG-HS8 wind guard, PAG-HS2 wind guards

For a complete list of available accessories, contact your LG representative.

For continual product development, LG reserves the right to change specifications without notice.

Operating Range:

Outdoor Unit:

Cooling (°F DB)	14-118
Heating (°F WB)	-13-65
1 1 11 21	

Indoor Unit:

Cooling (°F WB)	53-75
Heating (°F DB)	60-86

Unit Data:

Refrigerant Type	R410A
Refrigerant Control	EEV
Refrigerant Charge (lbs)	4.19
ODU Sound Pressure (Max) ±3 dB(A) ³	57
IDU Sound Pressure (H/M/L/Sleep) ±3 dB(A) ³	47/42/37/29
ODU Net Unit Weight (lbs)	122
ODU Shipping Weight (lbs)	131
IDU Net Unit Weight (lbs)	34
IDU Shipping Weight (lbs)	38
Heat Exchanger Coating	GoldFin™

Fan:

ODU Type		Propeller
IDU Type		Cross Flow
Fan Speeds (Fan/Cooling/Heating)		6/6/6
Quantity (ODU + IDU)		1 + 1
Motor/Drive Brushless Digitally Controlled/Dire		gitally Controlled/Direct
ODU Max Air Flow Rate (CFM)		2119
IDU Air Flow H/M/L (CFM)		565.0/423.7/317.8
Dehumidification (pts/hr)		4.7

Notes:

1.Acceptable operating voltage: 187V - 253V.

2. Piping lengths are equivalent.

3.Sound Pressure levels are tested in an anechoic chamber under ISO Standard 1996

4.All power/communication cable to be minimum 18 AWG, 4-conductor, stranded, shielded and must comply with applicable local and national code.

5.See Engineering Manual for sensible and latent capacities.

6. Power wiring cable size must comply with the applicable local and national code.

7. The indoor unit comes with a dry helium charge.

8.This data is rated 0 ft above sea level, with 24.6 ft of refrigerant line and a 0 ft level difference between outdoor and indoor units.

9. Must follow installation instructions in the applicable LG installation manual.






Outdoor Unit (ODU) - LAU240HYV1


Art Cool™ Pre Single Zone Inverter





Tag#:


Date:

















Air Discharge Grille	Gas Pipe Connection Port	Liquid Pipe Connection Port	Control Box	Sheath Heater	
1	2	3	4	2	
	1 Air Discharge Grille	1 Air Discharge Grille 2 Gas Pipe Connection Port	1 Air Discharge Grille 2 Gas Pipe Connection Port 3 Liquid Pipe Connection Port	1 Air Discharge Grille 2 Gas Pipe Connection Port 3 Liquid Pipe Connection Port 4 Control Box	

Indoor Unit (IDU) - LAN240HYV1

Art Cool™ Prestige Single Zone Inverter



Tag #:

Date:

