


Date:	For: <input type="checkbox"/> File <input type="checkbox"/> Resubmit
PO No.:	<input type="checkbox"/> Approval <input type="checkbox"/> Other _____
Architect:	GC:
Engr:	Mech:
Rep:	
(Company)	(Project Manager)



PRHR041A
Multi V™ Heat Recovery Unit



Performance:

Max Port Capacity Btu/h (each port)	54,000
Max Unit Capacity Btu/h (sum of ports)	192,000
Power Input (W)	40

Electrical:

Power Supply (V/Hz/∅)	208-230/60/1
Rated Amps (A)	0.16

Piping:

Refrigerant:

Port Liquid Line (in, OD)	3/8
Port Vapor Line (in, OD)	5/8
System Liquid Line (in, OD)	5/8
System Vapor Line High (in, OD)	7/8
System Vapor Line Low (in, OD)	1-1/8

Standard Features:

- Allows connected indoor units to be in cooling or heating mode simultaneously
- Internal components are insulated
 - External casing insulation is not needed¹
 - Condensate drain not needed
- Series or parallel connection with additional heat recovery units
- Flexible placement for service access or pipe routing
- Access panels
 - Top panel for solenoid valve heads
 - Rear panel for control access
 - Bottom panel for refrigerant circuit

Unit Data:

Refrigerant Type	R410A
Number of Indoor Unit Ports ²	4
Sound Pressure Data:	
Cooling Mode dB(A)	35.2
Heating Mode dB(A)	35.1
Simultaneous dB(A)	43.3
Net Unit Weight (lbs)	49
Shipping Weight (lbs)	57

Notes:

- 1.All refrigerant pipes require insulation.
- 2.Each port can allow up to 8 indoor units with a maximum capacity of 48 MBh per port.
- 3.All communication cable to be minimum 18 AWG, 2-conductor, stranded, shielded and must comply with applicable local and national code.
- 4.Kit components must be kept dry and free of debris before installation.
- 5.Must follow installation instructions in the applicable LG installation manual.
- 6.Power wiring cable size must comply with the applicable local and national code.
- 7.This unit comes with a dry nitrogen charge.




PRHR041A
Multi V™ Heat Recovery Unit




Tag #: _____

Date: _____

PO No.: _____



W	17-7/8"
H	8-5/8"
D	18-15/16"
L1	6-7/8"
L2	4-1/4"
L3	7-1/2"
L4	10-1/2"
L5	13-3/4"
L6	6-7/8"
L7	3-1/2"
L8	5-1/2"
L9	1-3/16"
L10	3-9/16"
L11	5-7/16"
L12	4-3/4"
L13	5-3/4"
L14	7-1/4"
L15	1-1/4"
M1	3-3/4"
M2	13-5/8"
M3	1-1/2"
M4	18-15/16"



Reducer Dimensions (in)					
		1	2	3	Quantity
Indoor Unit	Liquid Line	3/8 OD	1/4 OD	-	4
	Vapor Line	5/8 OD	1/2 OD	-	4
HR Unit	Liquid Line	1/2 OD	3/8 OD	-	2
	Vapor Line Low	3/4 OD	5/8 OD	-	2
		1-1/8 OD	7/8 OD	3/4 OD	2
	Vapor Line High	5/8 OD	1/2 OD	-	2
7/8 OD		3/4 OD	5/8 OD	2	